



TargetBlower

MODEL 6202E

The TargetBlower is a custom solution designed to control static in near critical environments. At 5V or better balance, it has the tightest specification of any ionizer in its class. The TargetBlower's space-saving design is perfect for point-of-use applications found in semiconductor final manufacturing and in other automated process tools. The collimated chassis¹ ensures directed ionized airflow at the target, efficiently eliminating hazardous static charge.


A self-maintaining balance system² and a patent-pending automatic cleaning system makes the TargetBlower a convenient device that delivers consistent, excellent performance without requiring time-consuming adjustments or maintenance.

Features and Benefits

- $\pm 5V$ balance or better
- Patent-pending, automatic emitter cleaning system
- Collimated chassis directs ionization to target area
- Enhanced features include Factory Monitoring System (FMS) connection and alarm LED
- Compact size with no separate control box
- Provides Class 0 (Charged Device Model) electrostatic protection to the most sensitive of devices
- Uninterrupted ionization is ensured with minimal user maintenance required
- Optimized point-of-use protection is perfect for automated in-tool applications
- Ionization status is easily monitored directly at the tool or from a remote location
- Charge protection for even the most space-limited automation tools

1. US Patent 7,295,418; 2. US Patent 6,118,645.

Specifications

| | |
|------------------------------|--|
| Input Voltage | 24 VDC, 5.5W max from external power supply (100-240 VAC, 50/60 Hz) or from tool power |
| Indicators | Green LED for power; red LED for alarm |
| Controls | Balance adjustment; fan high/off/low switch |
| Connectors | Telephone-style RJ handset input for external power supply or tool power; 2-pin terminal for FMS relay closure output |
| Ion Emission | Pulsed high frequency |
| Emitter Wire | Tungsten alloy corona wire |
| Airflow | 15 cfm, typical |
| Discharge | <4 sec @ 1 ft. ¹ |
| Balance | ±5V or better ¹ |
| Cleanroom Class | Meets ISO 14644-1 Class 5; Fed std. 209E Class 100 |
| Mounting | Two 6-32 mounting screw holes on bottom of blower |
| Operating Environment | Temperature 50-90°F (10-32°C); humidity 30-60% RH (non-condensing); up to ISO Cleanroom Class 7 (Federal Class 10,000) |
| Ozone | 0.015 ppm, typical (24-hour accumulation) |
| Chassis Material | Static dissipative plastic |
| Dimensions | 4.2H x 2.6W x 3.4D in. (10.7H x 6.5W x 8.7D cm) |
| Weight | 0.6 lb (272g) |
| Warranty | Two year limited warranty |
| Certifications | RoHS Compliant   |

1. Tested in accordance with ANSI/ESD STM3.1-2006.

Ordering Information

| | |
|-----------------|--|
| 91-6202e | TargetBlower includes an 8 ft, 4-pin cable for connecting Blower to power supply |
| 14-21106 | External power supply |
| 25-20660 | US Plug, 8.2 ft (2.5m) |
| 25-20710 | UK Plug, 8.2 ft (2.5m) |
| 25-20735 | German Schuko Plug, 8.2 ft (2.5m) |
| 25-20750 | China Plug, 8.2 ft (2.5m) |

Innovative Air Ionization Technology¹

The TargetBlower features a patented emitter wire design consisting of a thin filament electrode that generates a flowing ion airstream that produces greater ion generation. As a result, the TargetBlower is able to deliver excellent discharge times without the aid of external sensors in the close confines of tool equipment.

The self-cleaning ionization cleaning system is programmed to operate every seven days when the TargetBlower is on at any speed. This means that once the TargetBlower is installed, no continued maintenance is required, ensuring ionization without interruption.

Maintained Balance

After initial setup to meet the application environment specifications, no further adjustments to the TargetBlower are necessary. The TargetBlower features internal circuitry designed to ensure uninterrupted, balanced ionization performance.

Mounting Options

The TargetBlower's small size and unique form factor provides flexibility in choosing a mounting location that allows the best ESD protection.



The TargetBlower may be mounted in a variety of possible positions.



ION Systems

1750 North Loop Road
Alameda, CA 94502

Tel: 800.367.2452 (in USA)
Tel: 510.217.0600
info@ion.com
www.ion.com